

Overview

Product information



DF50-M-8AI-U-4-30050002668

Analog input module, 8-channel, voltage type

Product advantages

- The analog input module can receive $\pm 10V$, 0-10V standard signals.
- 8-channel analog input, voltage type.
- Two LED indicators indicate that the module is operating normally and communication is normal.
- Each input channel comes with an LED indicator light.
- Magnetic isolation between the on-site layer and the system layer.
- Transmit in 16 bit resolution.
- Protection level IP20.

Product certification

Technical data

Product drawing

3D model

□

Technical Information

Voltage measurement range	$\pm 10V$, 0-10V, 2-10V, $\pm 5V$, 0-5V, 1-5V
System feed current	<120mA
Reverse circuit protection	Yes
Error diagnosis	Yes
Working voltage	24V DC+20%/-15%
Voltage input accuracy (full temperature range)	$\pm 0.2\%$ (full range)
Diagnostic reporting function configuration	Support
Line type	2/3/4 wire system

Number of channels	8
Data size	16 Byte
Resolving power	16bit
Signal type	Single ended
Conversion time	60us/channel
Isolation method	Magnetic isolation from the on-site layer
Filtering time	Configurable

Environmental requirements

Protection type	IP20
working temperature	-25... 60 °C
Storage temperature	-40... 85 °C
relative humidity	5... 95% RH (condensation)

Wiring parameters

The maximum crimping area of the wire	1.5mm ²
	0.14mm ²
Maximum crimping area of wire (AWG)	AWG16
Connection technology: input/output	PUSH-IN type terminal blocks
Strip length	8-10mm
Installation method	DIN-35 type guide rail

Accessories

Business data

Order number	30050002668
Packing unit	1

Minimum order quantity	1
Products weight (without packaging)	60g