

Overview

Product information



DF50-M-8AO-U-4-30050002670

Analog output module, 8-channel, voltage type

Product advantages

- The analog output module can output voltage and current standard signals.
- 8-channel analog output, current type.
- Two LED indicators indicate that the module is operating normally and communication is normal.
- Magnetic isolation between the on-site layer and the system layer.
- Transmitted in 16 resolution format.
- Protection level IP20.

Product certification

Technical data

Product drawing

3D model

Technical Information

| | |
|--|---------------------|
| Overcurrent protection | Yes |
| Independent channel enable configuration | Support |
| Voltage output accuracy (full temperature range) | ± 0.5% (full range) |
| System feed current | <120mA |
| Error diagnosis | Yes |
| Working voltage | 24V DC+20%/-15% |
| Current output range | 0-20mA, 4-20mA |
| Number of channels | 8 |

| | |
|-------------------------|---|
| Data size | 16 Byte |
| Resolving power | 16bit |
| Signal type | Single ended |
| Conversion time | 60us/channel |
| Isolation method | Magnetic isolation from the on-site layer |
| Temperature coefficient | ≤ 50ppm/K |

Environmental requirements

| | |
|---------------------|----------------------------|
| Protection type | IP20 |
| working temperature | -25... 60 °C |
| Storage temperature | -40... 85 °C |
| relative humidity | 5... 95% RH (condensation) |

Wiring parameters

| | |
|---------------------------------------|------------------------------|
| The maximum crimping area of the wire | 1.5mm ² |
| | 0.14mm ² |
| Maximum crimping area of wire (AWG) | AWG16 |
| Connection technology: input/output | PUSH-IN type terminal blocks |
| Strip length | 8-10mm |
| Installation method | DIN-35 type guide rail |

Accessories

Business data

| | |
|------------------------|-------------|
| Order number | 30050002670 |
| Packing unit | 1 |
| Minimum order quantity | 1 |

Products weight (without
packaging)

60g